

LEAD FRAME, SEMICONDUCTOR DEVICE PRODUCED BY USING THE SAME AND
METHOD OF PRODUCING THE SEMICONDUCTOR DEVICE

BACKGROUND OF THE INVENTION

The present invention relates to a lead frame and more particularly to a lead frame loaded with photocoupling elements, a semiconductor device produced by using the lead frame, and a method of producing the semiconductor device.

A double sealed photocoupler belongs to a family of semiconductor devices. The double sealed photocoupler is produced by a procedure including primary sealing using light-transmitting resin and secondary sealing using light-intercepting resin. Japanese Patent Laid-Open Publication No. 9-83013, for example, discloses a double sealed photocoupler in which a lead frame for forming lead forming portions is accommodated in a secondary molding to thereby reduce the size of the photocoupler.

However, lead forming effected on a lead frame for bending the lead forming portions brings about the following problems. Portions where tie bars and opposite outside frames are connected irregularly deform. As a result, positioning holes formed in the outside frames are displaced and prevent the lead frame from being accurately positioned at a stage following the lead forming stage. Moreover, stress ascribable to lead forming remains in the individual

photocoupler or product and brings about package crack or similar trouble later.

SUMMARY OF THE INVENTION

5 It is therefore an object of the present invention to provide a lead frame free from deformation during lead forming while reducing the size of a semiconductor device to be loaded thereon, a semiconductor device produced by using the lead frame, and a method of producing the semiconductor device.

10 In accordance with the present invention, a lead frame includes a tie bar to which an element loading portion to be loaded with a semiconductor element is connected by a lead forming portion. An outside frame is formed with positioning holes. The tie bar is connected to the outside frame. A deformable portion is included in
15 the tie bar for preventing the outside frame from deforming.

 Also, in accordance with the present invention, in a semiconductor device including a pair of element loading portions loaded with semiconductor elements positioned one above the other and seal resin sealing the pair of element loading portions, leads
20 connected to a respective semiconductor element being exposed on said seal resin, only one of said pair of element loading portions is bent upward relative to said leads.

 Further, in accordance with the present invention, a method of producing a semiconductor device by using a frame includes a lead
25 forming step of bending lead forming portions after primary sealing

using light-transmitting resin, and a sealing step of sealing deformable portions included in a lead frame after the lead forming step.

5

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and advantages of the present invention will become more apparent from the following detailed description taken with the accompanying drawings in which:

FIGS. 1A through 1E are sections demonstrating a conventional
10 procedure for producing a double sealed photocoupler;

FIG. 2 is a section showing the configuration of another conventional photocoupler;

FIGS. 3A through 3C are isometric views for describing lead forming included in the conventional procedure for producing a
15 photocoupler;

FIGS. 4A through 4C are isometric views showing a lead frame embodying the present invention;

FIGS. 5A through 5E, 6A and 6B and 7A through 7C are views demonstrating a procedure for producing a semiconductor device by
20 using the lead frame of the illustrative embodiment;

FIG. 8 is a section for describing lead forming unique to the illustrative embodiment;

FIG. 9 is a plan view showing reinforcing portions also unique to the illustrative embodiment;

25 FIG. 10 is an isometric view for describing the influence of

deburring:

FIG. 11 is a view showing another specific configurations of a deformable portion included in the illustrative embodiment:

FIGS. 12A and 12B and 13 are sections for describing a configuration unique to the illustrative embodiment in which only one of two lead frames is depressed; and

FIG. 14 is a section showing a W type photocoupler to which the present invention is similarly applicable.

DESCRIPTION OF THE PREFERRED EMBODIMENT

To better understand the present invention, reference will be made to a conventional procedure for producing a double sealed photocoupler, shown in FIGS. 1A through 1E. While the production of a photocoupler is executed on a lead frame, FIGS. 1A through 1E do not show the entire lead frame. As shown, a lead frame 1a is depressed and loaded with a light emitting element 1 while a lead frame 2a is also depressed and loaded with a light-sensitive element 2. The lead frames 1a and 2a are paired in the position shown in FIG. 1A. The lead frames 1a and 2a are then positioned one above the other such that the light emitting element 1 and light-sensitive element 2 face each other, as shown in FIG. 1B.

Subsequently, as shown in FIG. 1C, light transmitting, primary seal resin 3a seals the light emitting element 1 and light-sensitive element 2 to thereby secure an optical path. More specifically, the primary seal resin 3a is configured as a rhombic cube. The lead

frames 1a and 2a each protrude from a particular apex of the rhombic cube. As shown in FIG. 1D, light intercepting, secondary seal resin 3b seals the primary seal resin 3a. Finally, as shown in FIG. 1E, the lead frames 1a and 2a are formed for mounting, thereby completing a photocoupler 4.

FIG. 2 shows another conventional photocoupler. As shown, the photocoupler, labeled 5, includes a primary molding 3a sealed by light transmitting, primary seal resin. Subsequently, the lead frames 1a and 2a loaded with the light emitting element 1 and light-sensitive element 2, respectively, are formed. Thereafter, secondary seal resin seals the primary molding 3a and lead frames 1a and 2a in the form of a secondary molding 3b.

Lead forming is effected with the photocoupler 4 after secondary sealing or effected with the photocoupler 5 after primary sealing, as stated above. A specific lead forming process executed after primary sealing will be described hereinafter.

FIGS. 3A through 3C demonstrate a conventional lead forming process applicable to a photocoupler. As shown, a plurality of (four in the specific procedure) photocouplers 6 each have two lead (terminal) forming portions 7a protruding from each of opposite ends. Each photocoupler 6 is connected to a lead frame 7 via the respective lead forming portions 7a. As shown in FIG. 3A, each lead forming portion 7a is connected to a first and a second tie bar 7b and 7c and an inner tie bar 7d. The tie bars 7b through 7d extend between two parallel, outside frames 7e.

More specifically, as shown in FIG. 7A, three tie bars 7b through 7d are arranged in parallel at each of opposite sides of the array of photocouplers 6 and extend substantially perpendicularly to the lead forming portions 7a. The outside frames 7e each are formed with holes 8 for positioning the lead frame 7.

The lead forming process begins after the primary sealing shown in FIG. 3A. First, as shown in FIG. 3B, the inner tie bars 7d are cut off while the first and second tie bars 7b and 7c are left. Subsequently, as shown in FIG. 3C, the lead forming portions 7a are bent between the individual photocoupler 6 and the first tie bars 7b (lead forming). Particularly, in the structure shown in FIG. 2, lead forming must be effected after the primary sealing in order to raise the primary molding 3a, which accommodates the light emitting element 1 and light-sensitive element 2.

The lead forming process described above has the following problems. When the lead forming portions 7a of the photocouplers 6 are bent on the lead frame 7, portions of the lead frame 7 where the tie bars 7b and 7c and outside frames 7e are connected irregularly deform, as shown in FIG. 3C. This is because the lead forming portions 7a bent by lead forming pull the tie bars 7b and 7c inward. As a result, the positioning holes 8 formed in the frames 7e are displaced and prevent the lead frame 7 from being accurately positioned at a stage following the lead forming stage. Moreover, stress ascribable to lead forming remains in the individual photocoupler 6 and brings about package crack or similar trouble

later.

Particularly, in the structure shown in FIG. 2, it is necessary to bend the leads before secondary sealing. Stress ascribable to the bending of the leads causes even the lead frame 7 loaded with photocouplers to deform by 0.2 mm or so. Such deformation disturbs the positional relation between the photocouplers and the positioning holes 8. This also obstructs accurate positioning after secondary sealing and therefor the production of photocouplers.

More specifically, lead forming is effected after the positioning holes 8 have been formed in the lead frame 7. Therefore, when the leads are bent, stress act on the holes 8 and cause them to deform. As a result, the holes 8 are displaced. The holes 8 are used to position the lead frame 7 before and after lead forming, and each has a relative positional relation with the individual photocoupler 6. The holes 8 are positioned at substantially the same interval. It is therefore important to maintain the accurate positional relation or distance between the holes 8 and the individual photocoupler 6. All stages on a production line rely on positioning based on the holes 8.

Referring to FIGS. 4A through 4C, a lead frame embodying the present invention will be described. FIGS. 4A and 4B show a lead frame 10a assigned to the light emission side and a lead frame 10b assigned to the light receiving side, respectively. FIG. 4C shows a frame for forming photocouplers, which are a specific form of semiconductor devices. The lead frames 10a and 10b are respectively

loaded with light emitting elements and light-sensitive elements, which will be described specifically later. The light emitting elements and light-sensitive elements may be implemented as LEDs (Light Emitting Elements) and phototransistors, respectively. The lead frame 10a is reversed in orientation and superposed on the lead frame 10b, so that the light emitting elements and light-sensitive elements face each other.

As shown in FIG. 4A, the lead frame 10a includes a pair of parallel, outside frames 11a and 11b, a first and a second tie bar 12a and 12b, an inner tie bar 12c for reinforcement, and a plurality of (four in the illustrative embodiment) element loading portions 13a. The tie bars 12a through 12c extend between the opposite frames 11a and 11b. Each element loading portion 13a is connected to the inner tie bar 12c and second tie bar 12b by two depressed, lead (terminal) forming portions 14. A light-sensitive element, not shown, is loaded on the rear surface of each element loading portion 13a face down and connected to preselected positions by metal wires although not shown specifically.

As shown in FIG. 4B, the lead frame 10b includes element loading portions 13b connected to an inner tie bar 12c and a second tie bar 12b by two lead forming portions 14. A light emitting element 17 is loaded on each element loading portion 13b and connected to preselected positions by metal wires although not shown specifically. The light emitting element 17 is coated with protection resin.

In FIGS. 4A and 4B, the first and second tie bars 12a and 12b

have substantially the same width that is greater than the width of the rod-like inner tie bar 12c. The second tie bars 12b each are connected to the frames 11a and 11b by deformable portions 15 at opposite ends thereof. The deformable portions 15 are implemented as rods having substantially the same diameter as the inner tie bars 12c, and each easily deforms at least in the direction parallel to the frames 11a and 11b. For example, each deformable portion 15 has a length one time or more greater than a width or has a width of about 0.3 mm, in which case the lead frame will be about 0.2 mm thick or less.

Holes 16 for positioning the lead frame 10a is formed in one outside frame 11a. The frames 11a and 11b are positioned at opposite sides of the array of element loading portions 13a. The first and second tie bars 12a and 12b and inner tie bar 12c are arranged in parallel at each of opposite sides of the element loading portions 13a and extend substantially perpendicularly to the lead forming portions 14. The lead forming portions 14 each are connected to the associated inner tie bar 12c.

The lead frame 10b is opposite in position to the lead frame 10a by 180 degrees in the direction of rotation. The element loading portions 13b of the lead frame 10b facing the element loading portions 13a are not depressed. The holes 16 of the lead frame 10b align with the holes 16 of the lead frame 10a. The lead frame 10b is therefore identical in configuration with the lead frame 10a in that it includes a pair of frames outside 11a and 11b, first and second tie bars 12a

and 12b, and inner tie bar 12c. As shown in FIG. 4B, light emitting elements 17 each are loaded on the front surface of a particular element loading portion 13b face up while facing, but not contacting, one of the light-sensitive elements loaded on the element loading portions 13a.

As shown in FIG. 4C, the frame 10c for producing semiconductor devices is prepared by laying the lead frame 10a over the lead frame 10b and welding or otherwise connecting them together. At this instant, the element loading portions 13a overlie the element loading portions 13b. The holes 16 of the lead frames 10a and 10b are exposed to the outside. The frames 11a and 11b are joined together. In this manner, in the frame 10c, only the lead frame 10a has the element loading portions 13a stepped relative to the associated lead forming portions 14.

With the frame 10c, it is possible to produce an optical MOS (Metal Oxide Semiconductor) or similar photocoupler that optically couple a light emitting side and a light-sensitive side. Reference will be made to FIGS. 5A through 5E, 6A, 6B and 7A through 7C for describing a procedure for producing such a photocoupler. First, as shown in FIG. 5A, the lead frame 10a having the element loading portions 13a loaded with the light-sensitive elements 18, FIG. 4A, and the lead frame 10b having the element loading portions 13b loaded with the light emitting elements 17, FIG. 4B, are prepared. As shown in FIG. 5B, the lead frames 10a and 10b are combined such that the light emitting elements 18 and light-sensitive elements face each

other, but do not contact each other, thereby constituting the frame 10c, FIG. 4C.

Each light-sensitive element 18 is bonded to the respective element loading portion 13a by wires 19. Each light emitting element 17 is precoated with, e.g., transparent silicone resin and then bonded to the respective element loading portion 13b by wires 19.

Subsequently, as shown in FIGS. 5C and 6A, each light emitting element 17 and associated light-sensitive element 18 of the frame 10c are sealed by light transmitting, primary seal resin 20 in order to secure an optical path. The seal resin 20 is configured as a trapezoidal cube. The lead forming portions 14 protrude from the portions of opposite slants of the trapezoidal cube close to the bottom. After the primary sealing, the inner tie bars 12c are cut off while the first and second tie bars 12a and 12b are left. As a result, the seal resin 20 is connected to each second tie bar 12b by two lead forming portions 14 while each tie bar 12b is connected to the frame 11a or 11b via the deformable portions 15. Stated another way, as shown in FIG. 6B, the seal resin 20 is connected to the frames 11a and 11b only by the deformable portions 15, which are easily deformable in the direction parallel to the frames 11a and 11b like, e.g., hanging pins.

As shown in FIGS. 5D and 7A, the lead forming portions 14 are bent between the primary seal resin 20 and the second tie bars 12b (inner lead forming) in order to raise the seal resin 20. More specifically, the lead forming portions 14 are bent while being

crushed and thereby locally thinned and extended.

As shown in FIGS. 5E and 7B, an optical coupling device to be produced by using the frame 10c has two lead forming portions 14 accommodated in secondary seal resin 21, as will be described hereinafter. It is therefore necessary to execute lead forming after the primary sealing in order to raise the primary seal resin 20. The lead forming forms a step substantially corresponding to the thickness of the bottom of the secondary seal resin 21.

The lead forming step that bends the lead forming portions 14 while crushing them will be described specifically with reference to FIG. 8. Assume the step in which after the cutting of the inner tie bars 12c following the primary sealing, each primary seal resin 20 and frames 11a and 11b are supported only by the deformable portions 15. In this condition, an upper and a lower mold 22 sandwich each lead forming portion (inner lead) 14 so as to press it downward while crushing it. Consequently, part of the lead forming portion 14 crushed and bent is extended to a thickness that is substantially three-fifths of the original thickness of the lead forming portion 14. The thin, extended part absorbs the distance over which the lead forming portion 14 is pulled during deformation, thereby reducing deformation. This successfully prevents lead forming from influencing the frame 10c. Experiments showed that for a designed amount of deformation of about 0.223 mm, the actual amount of deformation was about 0.07 mm, i.e., about one-third of the designed amount.

The deformation of each lead forming portion 14 pulls the second tie bar 12b inward toward the primary seal resin 20 during the above lead forming. However, the deformable portion 15 deforms and surely, sufficiently absorbs the force, which pulls the tie bar 12b, in combination with the crushing and bending operation, as shown in FIG. 7A. More specifically, the deformable portion 15 is configured to absorb stress acting on the tie bar 12b, which is crushed and bent, by deforming itself in the direction parallel to the frames 11a and 11b. The tie bar 12b and frames 11a and 11b are therefore free from deformation described with reference to 3C and prevent the holes 16 of the frames 11a and 11b from being displaced due to irregular deformation.

As shown in FIGS. 5E and 7B, after the lead forming described above, the light intercepting, secondary seal resin 21 seals the primary seal resin 20 in order to shield extraneous light. At the same time, the secondary seal resin 21 seals the deformable portions 15 (four in FIG. 7B) to thereby form reinforcing portions 23 for reinforcing the portions 15. The reinforcing portions 23 constitute dummy packages not containing any product.

FIG. 9 shows how the reinforcing portions 23 are formed more specifically. As shown, each reinforcing portion 23 extends over the associated first and second tie bars 12a and 12b while sandwiching them from opposite sides. The reinforcing portion 23 covers not only the deformable portion 15 connecting the frame 11a or 11b and second tie bar 12b, but also the portion of the first tie bar 12a connected

to the frame 11a or 11b.

Subsequently, deburring is executed with the double sealed product portions or package portion by using, e.g., a water jet. After deburring, the leads are plated, and then the lead forming portions 14 of the individual package are cut to a necessary length. Finally, as shown in FIG. 7C, the package is removed from the frame 10c to thereby complete a photocoupler 25 for planar mounting. The leads 24 of the photocoupler 25 are positioned at the bottom of the package sealed by the secondary seal resin 21 or the extension thereof.

During deburring, a downward force acts on the product portions sealed by the secondary seal resin 21. However, the deformable portions connected to the second tie bars 12b and frames 11a and 11b are reinforced by the reinforcing portions 23 and therefore prevent the product portions from being deformed downward.

The influence of deburring will be described with reference to FIG. 10. As shown, when a downward pressure acts on the individual product portion sealed by the secondary seal resin 21, the product portion deforms downward together with the second tie bars 12b because it is supported by the frames 11a and 11b via the deformable portions 15. More specifically, the product portions are connected to the frames 11a and 11b by the deformable portions 15 and therefore easily displaced. This is particularly true when the product portions are cleaned by a water jet before plating. However, the reinforcing portions 23 reinforcing the deformable portions 15 prevent the

portions 15 from deforming, i.e., prevent the product portions from deforming via the second tie bars 12b that include the portions 15.

FIG. 11 shows specific configurations of each deformable portion 15. In the illustrative embodiment, the deformable portion 15 is implemented as a hanging pin, as stated earlier. As shown in FIG. 11, the deformable portion 15 may be replaced with a deformable portion 15a larger in diameter at opposite end portions than at the intermediate portion or a deformable portion 15b bent in the form of narrow steps. Further, use may be made of a deformable portion 15c consisting of a plurality of (e.g. two) pieces. The crux is that the deformable portion be easily deformable in the direction parallel to the frames 11a and 11b, absorbing a force that pulls the second tie bars 12b inward toward the element loading portions.

FIGS. 12A and 12B show the structure of the frame 10c in which the lead frame 10a is depressed while the lead frame 10b is not depressed. As shown in FIG. 12A, one of the frames or lead forming portions 14 is depressed while the other is left flat. By contrast, as shown in FIG. 12B, a conventional structure has both frames 1a and 1b, which are respectively assigned to the light emission side and light receiving side, depressed by substantially the same amount.

As FIG. 12A indicates, in the illustrative embodiment, only one of the frames 10a and 10b is depressed deeply enough to allow the other frame to remain flat. Moreover, in FIG. 12A, the product portion is raised, or shifted, by an amount a in order to guarantee the thickness of the secondary seal resin. The amount of shift a is

smaller than the amount of shift b required of the conventional product portion shown in FIG. 12B. This not only reduces the deformation of the frames 10c ascribable to lead forming, but also promotes easy processing of the frame 10c.

5 As shown in FIG. 13, in the photocoupler having the structure described above, only the light emitting element generate heat during operation. It is therefore important to release the heat for enhancing the reliability of the semiconductor device. Generally, most of the heat generated by the light emitting element is propagated
10 through the lead frame (13b), as indicated by hatching in FIG. 13. Therefore, if the distance between the light emitting element and the mounting surface c of a circuit board is reduced, then the heat can be efficiently released to the circuit board.

More specifically, in the photocoupler 25 of the illustrative
15 embodiment, FIG. 7C, the leads or lead forming portions 14 are accommodated in the secondary seal resin 21 while the terminals are exposed at the bottom of the seal resin 21. In this configuration, a distance d' between the light emitting element and the mounting
20 surface c (heat path d' hereinafter) is shorter than the conventional distance. Further, the heat path of the photocoupler 25 is shorter than the heat path of another conventional configuration shown in FIG. 2. The illustrative embodiment therefore reduces thermal resistance, i.e., the temperature elevation of a chip itself relative to power
25 consumption and thereby enhances the reliability of a product, compared to the conventional configuration.

As stated above, the lead frame of the illustrative embodiment includes the plastically deformable portions 15. A photocoupler using such a lead frame is produced by a procedure including a lead forming step or crushing and bending step and a step of forming the reinforcing portions 23 around the deformable portions 15. More specifically, in the inner lead forming step following the primary sealing step, portions formed of an easy-to-deform material and provided with an easy-to-deform configuration are formed between the lead frame and the product portions beforehand, so that the positional relation between the former and the latter does not vary. The above portions deform to prevent deformation from being transferred to the frame.

Further, the reinforcing portions 23 protect the product portions from deformation in subsequent stages (particularly the deburring stage) ascribable to the deformable portions 15 that would otherwise reduce the strength of the product portions. This successfully reduces a mounting area to be allocated to, e.g., a double sealed photocoupler. In addition, deformation ascribable to lead forming is not transferred to the lead frame, so that the positioning holes 16 and product portions are maintained in the preselected positional relation. The reduction of deformation from about 0.223 to about 0.07 mm, i.e., by about one-third is particularly significant. Considering the state-of-the-art lead frame as thin as about 0.2 mm, a displacement of about 0.2 mm would result in the loss of the secondary seal resin for intercepting light.

Moreover, the deformable portions 15 compensate for some bend of the portions where the product forming portions and lead frame join each other. In addition, the lead frame is scarcely pulled during lead forming because only one of the element loading portions is bent upward above the associated leads. This is also successful to maintain the preselected positional relation between the product forming portions and the lead frame; otherwise the holes 16 would be displaced and make the following steps impracticable.

In the illustrative embodiment, the frame 10c has the lead frames 10a and 10b combined together with the former overlying the latter. Alternatively, the lead frames 10a and 10b may be shifted in the horizontal direction and constructed integrally with each other with the frames 11a and 11b thereof not overlapping each other.

FIG. 14 shows a specific W type photocoupler to which the present invention is similarly applicable. As shown, the W type photocoupler, labeled 26, includes liquid seal resin 27 in place of the primary molding in order to form an optical path.

In summary, in accordance with the present invention, a lead frame includes a plurality of tie bars including tie bars each having deformable portions that protect outside frames from deformation. The outside frames are formed with positioning holes. Element loading portions to be loaded with semiconductor elements are connected to the outside frames by such tie bars. The lead frame is therefore free from deformation during lead forming while promoting the miniaturization of the semiconductor devices.

Various modifications will become possible for those skilled in the art after receiving the teachings of the present disclosure without departing from the scope thereof.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
223